

PETRO FACTS



SONIC® MP GEAR OIL

is available in:

- 12 x 1 litre case (80W90 only)
- 4 x 5 litre case
- 60 litre keg (80W90 only)
- 20 litre pail
- 110 litre drum
- 205 litre drum

(Note: Not all grades are available in every container size.)



SONIC® MP GEAR OIL

WITH CGT

DESCRIPTION

SONIC® MP GEAR OIL is formulated to provide superior lubrication in passenger cars, farm equipment, heavy and light-duty trucks, off-highway equipment and industrial gear applications. It has CGT (Clean Gear Technology) to reduce deposits on gear deposits, extend equipment life, and extend fluid life.

FEATURES & BENEFITS

- **LIMITED SLIP COMPATIBLE**
Formulated for top-up or complete refill of limited slip differential.
- **GEAR PROTECTION**
Extreme pressure additives offer superior gear protection under high loads.
- **COMPATIBILITY**
MP Gear Oil is compatible with commonly used seal material.
- **WATER TOLERANT**
Excellent for applications where water contamination may occur.
- **OXIDATION STABILITY**
Reduces deposits on gear trains under high operating temperature conditions.
- **CORROSION PROTECTION**
Offers excellent protection against rust and corrosion, even in stationary applications.

APPLICATION

- **SONIC MP GEAR OIL** is recommended for use in any application requiring a heavy-duty, extreme-pressure gear lubricant. Special additive chemistry also makes it suitable for **top-up** and **complete refill** of limited slip differential.

QUALIFICATIONS

- **MEETS OR EXCEEDS SPECIFICATIONS:**

API	GL5	MILITARY	MIL-L-2105E
MACK	GO-J	FORD	Limited Slip Applications

TYPICAL PROPERTIES

● SAE GRADE	75W	75W90	80W90	85W140
Viscosity @40°C, cst	50	89.5	160	319
Viscosity @100°C, cst	5.5	14.6	15.8	30.1
Viscosity Index	135	110	110	98
Pour Point, 0°C	-36°C	-42°C	-30°C	-15°C

RECYCLABLE
WHERE FACILITIES EXIST

Printed in Canada
with vegetable-based inks